Technical Specifications

9 28VDC
typ. 0.28W
1-Wire: max. 20 sensors, max. 50mA or one iButton key reader max. wire length depending on wiring topology: 100 300m
Loxone Link: connection with Miniserver
0.31W
-40 70°C / -40 158°F
max. 95% r. H. (non condensing
IP20
35.5x88x57mm / 1.4x3.46x2.24" (LxWxH)
This device is free of main- tenance and may only be cleaned with a dry cloth.

1-wire interface

Wire cross-section	0.14 0.5mm² / AWG26 20
Stripping length	7mm / 0.28"
Temperature resistance	-40 70 °C / -40 158°F

LOXONE

LOXONE

Loxone **Electronics GmbH** Loxone UK

Theale, RG7 4RA



For additional information. www.loxone.com/datasheets

1-Wire Extension

Need Help?



Part No: 100014

About the product

The Loxone 1-Wire Extension is a device for automatic control and management of home automation and similar non safety critical applications.

Installation & electrical connection

The installation of the devices has to be mounted on a DIN rail in an electrical distribution housing (Standard distribution) and may only be performed by qualified personnel.

Protection against electrical contact and fire protection must be provided in the final installation by the use of a standards compliant/approved housing.

To turn the unit on/off during installation and in case of failure, a separator (disconnecting device) must be present. These must be easily accessible and visible. If the unit is used in a non conform manner as specified by the manufacturer the product included safeguards will be impaired.

Power Supply and Loxone Link

Wire cross-section	0.25 0.8mm² / AWG23 18
Stripping length	5mm / 0.2"
Temperature resistance	-40 105°C / -40 221°F

This folder is a part of the product!



For additional information, visit www.loxone.com/help/1-wire

